



ZPMV2.E234136

Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

WM ELTAR

E234136

Spolka z ograniczona odpowiedzialnoscia Sp k

Ul Cmentarna 5

42-600 Tarnowskie Gory, POLAND

	Cond Width		Cond	SS/ DS/ DSO	Max		Max		Meets	C
	Min	Edge			Area	Solder	Oper	Temp		
Type	mm(in)	mm(in)	Thk mic(mil)	DSO	Diam mm(in)	Limits C sec	Temp C	Flame Class	UL796 DSR	T I
Single layer printed wiring boards.										
C	0.23 (0.009)	0.38 (0.015)	16.5 (0.65)	DS	38.1 (1.5)	260 10	125	V-0	All	*
D	0.23 (0.009)	0.38 (0.015)	16.5 (0.65)	DS	101.6 (4.0)	260 10	125	V-0	▲	*
E	0.23 (0.009)	0.38 (0.015)	16.5 (0.65)	DS	101.6 (4.0)	260 10	125	V-0	▲	*
S	0.23 (0.009)	0.38 (0.015)	16.5 (0.65)	DS	101.6 (4.0)	260 10	125	V-0	▲	*

DSR - Where the Direct Support Requirements column shows a solid triangle, the individual PCB may be marked when it is in compliance with the DS requirements

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark
factory identification or burning test classification.

or file number and type designation. May be followed by a suffix to denote

[Last Updated](#) on 2018-01-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".